


<< Inductive Sensor

Metal Barrel-KH08SS



Description:


Stainless steel housing, smooth barrel, DC 3-wire output, IP67 protection class, LED indicator, super short size.

Technical Data:

Type	Rated Operating Distance S_n	Mounting	Output	Voltage Range U_B	Rated Current	Switching Frequency	Ambient Temperature	Connection	Fig
Fi2-KH08SS-OP6L	2mm	Flush	PNP NO	10...30VDC	$\leq 200\text{mA}$	1000Hz	-25...70°C	2m cable	Fig.1
Fi2-KH08SS-ON6L	2mm	Flush	NPN NO	10...30VDC	$\leq 200\text{mA}$	1000Hz	-25...70°C	2m cable	Fig.1
Fi2-KH08SS-CP6L	2mm	Flush	PNP NC	10...30VDC	$\leq 200\text{mA}$	1000Hz	-25...70°C	2m cable	Fig.1
Fi2-KH08SS-CN6L	2mm	Flush	NPN NC	10...30VDC	$\leq 200\text{mA}$	1000Hz	-25...70°C	2m cable	Fig.1

Dimensions:

Fig.1



Metal Barrel-KH08SS



Description:

Stainless steel housing, smooth barrel, DC 2-wire output, IP67 protection class, LED indicator, super short size.

Technical Data:

Type	Rated Operating Distance S_n	Mounting	Output	Voltage Range U_B	Rated Current	Switching Frequency	Ambient Temperature	Connection	Fig
Fi2-KH08SS-OD6L	2mm	Flush	DC NO	10...30VDC	≤100mA	1000Hz	-25...70°C	2m cable	Fig.1
Fi2-KH08SS-CD6L	2mm	Flush	DC NC	10...30VDC	≤100mA	1000Hz	-25...70°C	2m cable	Fig.1

Dimensions:

Fig.1

